



Standard Specifications

ITEM		SPECIFICATION		
Standard Dimension	(SS5-34)	<u>Length</u>	<u>Width</u>	<u>Height</u>
		194.3 x 72.4 x 106.7 cm		
	(MX-600)	76.5 x 28.5 x 42 in		
		217.4 x 81.3 x 104.1 cm		
	(SS5-36)	86 x 32 x 41 in		
	(SS5-46)	219.7 x 76.2 x 104.1 cm		
		86.5 x 30 x 41 in		
	(SS5-46)	226.1 x 76.2 x 104.1 cm		
		89 x 30 x 41 in		
Bed Size	(MX-600)	68.6L X 76.2W cm (27L X 30W in)		
	(SS5-34)	59.7L X 69.9W cm (23.5L X 27.5W in)		
	(SS5-36, 5-46)	49.5L X 73.7 cm (19L X 30W in)		
Dry Weight (Including Batteries)	(SS5-36 & MX-600)	352 kg (775 lbs)		
	(SS5-34)	332 kg (713 lbs)		
	(SS5-46)	376 kg (830 lbs)		
Turning Radius	(MX-600)	205 cm (81 in)		
	(SS5-34 & SS5-36)	190.5 cm (75 in)		
	(SS5-46)	208.7 cm (81 in)		
Brakes	(SS5-36, 5-46, MX-600) (SS5-34)	2-Wheel Rear Drum (Mechanical Standard) Drive Line Brake Band		
Motor		24 Volts, 4.5 hp @ 935 rpm		
Tires		4.80 X 8 Load Range B Pnuematic		
Tire Presure		50 psi max.		
Maximum Load (On Level Surface)	(MX-600, SS5-36, 5-34)	272 kg (600 lbs.)		
	(SS5-34)	227 kg (500 lbs)		
Battery		Four 217 AH, 6 Volt		
Charger		120V, 12Amp, 60Hz AC Input 24V, 25Amp DC Output		
Gradeability		15% (Empty) 5% (Loaded)		
Maximum Speed (Empty)		16 kmh (10 mph)		